## **CERTIFICATE**OF COMPLIANCE



## LG Hausys America, Inc.

LG Hausys HI-MACS®

Restrictions: with or without LG HI-MACS® joint adhesive

4007-410

Certificate Number

08/13/2007 - 08/13/2018

Certificate Period

Certified

Status

UL 2818 - 2013 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

 $Building\ materials\ are\ determined\ compliant\ in\ accordance\ with\ an\ Office\ environment\ with\ an\ air\ change\ of\ o.68\ hr^{-1}\ and\ a\ loading\ of\ 3.20\ m^2.$ 

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



**Environment** 

## **GREENGUARD Certification Criteria for Building Products and Interior Finishes**

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.50	mg/m³
Formaldehyde	50-00-0	61.3 (50 ppb)	μg/m³
Total Aldehydes (B)	-	0.10	ppm
Particle Matter less than 10 μm (C)	-	50	μg/m³
4-Phenylcyclohexene	4994-16-5	6.5	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

- (A) Defined to be the total response of measured VOCs falling within the C6 C16 range, with responses calibrated to a toluene surrogate.

  Maximum allowable predicted TVOC concentrations for GREENGUARD (0.50 mg/m³) fall in the range of 0.5 mg/m³ or less, as specified in CDPH Standard Method v1.1.
- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- (C) Particle emission requirement only applicable to HVAC Duct Products with exposed surface area in air streams (a forced air test with specific test method) and for wood finishing (sanding) systems.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



## **Environment**